

APL/MP

Pressore liscio a sfera e molla

Smooth ball spring plunger

Presor liso a esfera y resorte



Materiale

Corpo in ottone. Sfera in tecnopolimero, rinforzato con fibre di vetro. Molla in acciaio inox AISI 303.

Brass body. Thermoplastic ball, glass fiber reinforced. Stainless steel spring (AISI 303).

Cuerpo de latón. Esfera de termoplástico, reforzado con fibra de vidrio. Resorte de acero inoxidable (AISI 303).

Codice	Modello	L mm	l2 mm	d1 mm	V mm	D mm	l3 mm	F1 N	F2 N	Peso gr.
7747033	APL/3MP	4,0	0,6	3	Ø2,5	3,5	0,7	1,7	3,6	0,2
7747034	APL/4MP	5,0	1	4	Ø3,0	4,6	0,7	3	7	0,4
7747035	APL/5MP	6,0	1	5	Ø4,0	5,6	1,0	4	7	0,6
7747036	APL/6MP	7,0	1	6	Ø5,0	6,5	1,5	6	12	1,1
7747037	APL/8MP	9,0	1	8	Ø6,5	8,5	1,8	6	12	2,2
7747038	APL/10MP	13,5	1,9	10	Ø8,0	11,0	3,0	10	20	5,0
7747039	APL/12MP	16,0	2,5	12	Ø10,0	14,0	3,5	13	25	7,7



NOTE: F1: Pressione molla precarico. F2: Pressione molla carico max.

F1: Spring pressure preload. F2: Spring pressure max load.

F1: Presión de resorte precarga. F2: Presión de resorte carga máxima.

