

PSDA PSDA/C

Pistoncino a molla
Indexing plunger
Posicionador con resorte



Materiale

Corpo in acciaio zincato. Anello, puntale e molla in acciaio inox AISI 303.

Zinc plated steel body. Stainless steel ring, pin and spring (AISI 303).

Cuerpo de acero galvanizado. Anillo, puntera y resorte de acero inoxidable (AISI 303).

Codice	Modello	d1 mm	D	L mm	l1 mm	l2 mm	l3 mm	d2 mm	Y mm	m mm	Peso gr.
6394105	PSDA/14	14	M6	16,5	11	12	4	4	6	-	3,3
6394110	PSDA/18	18	M8	22	15	16	5	5	8	-	7,6
6394115	PSDA/24	24	M10	27,5	19	20	6	6	10	-	16,7
6394120	PSDA/30	30	M12	33	23	24	8	8	12	-	29,0
6394106	PSDA/14/C	14	M6	16,5	11	12	4	4	6	4	5,0
6394111	PSDA/18/C	18	M8	22	15	16	5	5	8	5	11,2
6394116	PSDA/24/C	24	M10	27,5	19	20	6	6	10	6	24,0
6394121	PSDA/30/C	30	M12	33	23	24	8	8	12	7	39,5

NOTE: Versione C con controddado in acciaio zincato.

C version with zinc plated steel locking nut.

Versión C con contratuerca de acero galvanizado.

