

PSDX PSDX/C

Pistoncino a molla
Indexing plunger
Posicionador con resorte



Descrizione

Corpo e puntale in acciaio inox AISI 303.

Stainless steel body and pin (AISI 303).


Cuerpo y puntera de acero inoxidable (AISI 303).

Materiale

Volantino zigrinato in tecnopolimero nero, rinforzato con fibre di vetro, finitura opaca.

Black thermoplastic knurled knob, glass fiber reinforced, mat.

Volante moleteado de termoplástico negro, reforzado con fibra de vidrio, acabado mate.



Codice	Modello	D	d1 mm	L mm	l1 mm	l2 mm	l3 mm	l4 mm	d2 mm	Y mm	m mm	F1 mm	F2 mm	Peso gr.
7747770	PSDX/12	M6	12	31	10,0	12	4	16,5	4	6	-	3	12	5
7747775	PSDX/16	M8	16	40	13,5	16	5	22,0	5	8	-	5	22	10
7747780	PSDX/18	M10	18	49	17,0	20	6	27,5	6	10	-	5	22	19
7747785	PSDX/21	M12	21	59	20,5	24	8	33,0	8	12	-	6	22	33
7747771	PSDX/12/C	M6	12	31	10,0	12	4	16,5	4	6	4	3	12	6
7747776	PSDX/16/C	M8	16	40	13,5	16	5	22,0	5	8	4	5	22	11
7747781	PSDX/18/C	M10	18	49	17,0	20	6	27,5	6	10	5	5	22	24
7747786	PSDX/21/C	M12	21	59	20,5	24	8	33,0	8	12	6	6	22	41

NOTE: Versione C con controdado in acciaio inox AISI 303. F1: Pressione molla precarico. F2: Pressione molla carico max.

C version with stainless steel locking nut (AISI 303). F1: Spring pressure preload. F2: Spring pressure max load.

Versión C con contratuerca de acero inoxidable (AISI 303). F1: Presión de resorte precarga. F2: Presión de resorte carga máxima.