

# ACFF

**Antivibrante cilindrico**  
**Cylindrical anti-vibration**  
**Antivibratorio cilíndricos**



## Descrizione

### Bussola in acciaio zincato e foro cieco filettato.

Zinc plated steel insert and tapped blind hole.


Inserto de acero galvanizado y agujero ciego roscado.

## Materiale

### Gomma naturale nera, durezza 60±5 Shore A.

Black natural rubber, hardness 60±5 Shore A.

Goma natural negra, dureza de 60±5 Shore A.



Codice	Modello	A mm	C mm	D	E mm	Carico Statico a compressione (maximum) Compressive static load. Carga estática (máxima) por compresión. Kg.	Carico Statico a taglio (maximum) Shearing static load. Carga estática (máxima) por cortes Kg.
7330299	ACFF/10x15 M4	10	15	M4	4	18,5	4
7330300	ACFF/10x15 M5	10	15	M5	5	18,5	4
7330305	ACFF/15x15 M4	15	15	M4	5	19	4
7330310	ACFF/15x15 M5	15	15	M5	5	19	4
7330314	ACFF/15x20 M4	15	20	M4	4	20	4
7330315	ACFF/15x20 M5	15	20	M5	5	20	4
7330320	ACFF/20x15 M6	20	15	M6	6	31	5
7330325	ACFF/20x20 M6	20	20	M6	6	40	5
7330330	ACFF/20x25 M6	20	25	M6	6	30	4
7330335	ACFF/20x30 M6	20	30	M6	6	30	4
7330340	ACFF/25x15 M6	25	15	M6	6	48	5
7330345	ACFF/25x20 M6	25	20	M6	6	54	6
7330350	ACFF/25x20 M8	25	20	M8	8	48	5
7330355	ACFF/25x25 M6	25	25	M6	6	40	4
7330360	ACFF/25x30 M6	25	30	M6	6	39	4
7330365	ACFF/25x35 M6	25	35	M6	6	37	4
7330367	ACFF/30x15 M8	30	15	M8	8	74	8
7330370	ACFF/30x20 M8	30	20	M8	8	72	8
7330375	ACFF/30x25 M8	30	25	M8	8	67	8
7330380	ACFF/30x30 M6	30	30	M6	6	61	8
7330385	ACFF/30x30 M8	30	30	M8	8	61	8
7330390	ACFF/30x40 M8	30	40	M8	8	70	7
7330393	ACFF/35x35 M8	35	35	M8	8	95	11
7330395	ACFF/40x20 M8	40	20	M8	8	120	16
7330398	ACFF/40x30 M6	40	30	M6	6	120	16
7330400	ACFF/40x30 M8	40	30	M8	8	120	16
7330405	ACFF/40x30 M10	40	30	M10	10	120	16
7330410	ACFF/40x35 M8	40	35	M8	8	108	18

**NOTE:** Si forniscono, per quantità adeguate, durezza minori o superiori a 60 Shore A e inserti a misura.

For certain quantities, it can be supplied with a hardness higher or lower than 60 shore A and with inserts of different measures.

Por cantidad apropiada disponible también con dureza superior o inferior a 60 shore A y con insertos de distintas medidas.

# ACFF

**Antivibrante cilindrico**  
**Cylindrical anti-vibration**  
**Antivibratorio cilíndricos**



## Descrizione

### Bussola in acciaio zincato e foro cieco filettato.

Zinc plated steel insert and tapped blind hole.


Inserto de acero galvanizado y agujero ciego roscado.

## Materiale

### Gomma naturale nera, durezza 60±5 Shore A.

Black natural rubber, hardness 60±5 Shore A.

Goma natural negra, dureza de 60±5 Shore A.



Codice	Modello	A mm	C mm	D	E mm	Carico Statico a compressione (maximum) Compressive static load. Carga estática (máxima) por compresión. Kg.	Carico Statico a taglio (maximum) Shearing static load. Carga estática (máxima) por cortes Kg.
7330415	ACFF/40x40 M8	40	40	M8	8	97	18
7330417	ACFF/40x40 M10	40	40	M10	10	95	18
7330420	ACFF/50x20 M10	50	20	M10	10	160	20
7330422	ACFF/50x25 M10	50	25	M10	10	160	20
7330425	ACFF/50x30 M10	50	30	M10	10	160	20
7330427	ACFF/50x35 M10	50	35	M10	10	164	19
7330430	ACFF/50x40 M10	50	40	M10	10	168	18
7330435	ACFF/50x45 M10	50	45	M10	10	158	18
7330440	ACFF/50x50 M10	50	50	M10	10	150	14
7330442	ACFF/50x55 M10	50	55	M10	10	142	10
7330445	ACFF/60x30 M12	60	30	M12	12	250	40
7330450	ACFF/60x35 M12	60	35	M12	12	250	40
7330455	ACFF/60x40 M12	60	40	M12	12	240	35
7330460	ACFF/60x45 M12	60	45	M12	12	235	32
7330465	ACFF/60x50 M12	60	50	M12	12	227	25
7330470	ACFF/60x55 M12	60	55	M12	12	218	25
7330475	ACFF/60x60 M12	60	60	M12	12	210	23
7330480	ACFF/75x25 M12	75	25	M12	12	285	60
7330485	ACFF/75x30 M12	75	30	M12	12	285	60
7330490	ACFF/75x35 M12	75	35	M12	12	280	50
7330495	ACFF/75x40 M12	75	40	M12	12	280	50
7330500	ACFF/75x50 M12	75	50	M12	12	275	50
7330505	ACFF/75x55 M12	75	55	M12	12	270	48
7330510	ACFF/75x60 M12	75	60	M12	12	260	45
7330515	ACFF/100x40 M16	100	40	M16	16	775	110
7330520	ACFF/100x50 M16	100	50	M16	16	770	100
7330525	ACFF/100x55 M16	100	55	M16	16	740	100
7330530	ACFF/100x60 M16	100	60	M16	16	710	95

**NOTE:** Si forniscono, per quantità adeguate, durezza minori o superiori a 60 Shore A e inserti a misura.

For certain quantities, it can be supplied with a hardness higher or lower than 60 shore A and with inserts of different measures.

Por cantidad apropiada disponible también con dureza superior o inferior a 60 shore A y con insertos de distintas medidas.