

ACPF

Antivibrante cilindrico
Cylindrical anti-vibration
Antivibratorio cilíndricos



Descrizione

Bussola in acciaio zincato e foro cieco filettato.

Zinc plated steel insert and tapped blind hole.


Inserto de acero galvanizado y agujero ciego roscado.

Materiale

Gomma naturale nera, durezza 60±5 Shore A.

Black natural rubber, hardness 60±5 Shore A.

Goma natural negra, dureza de 60±5 Shore A.



Codice	Modello	A mm	C mm	D	E mm	Carico Statico a compressione (maximum) Compressive static load. Carga estática (máxima) por compresión. Kg.
7331100	ACPF/15x20 M4	15	20	M4	4	10
7331104	ACPF/20x10 M6	20	10	M6	6	28
7331108	ACPF/20x20 M6	20	20	M6	6	20
7331112	ACPF/20x30 M6	20	30	M6	6	16
7331116	ACPF/25x15 M6	25	15	M6	6	35
7331120	ACPF/25x25 M6	25	25	M6	6	28
7331124	ACPF/25x30 M6	25	30	M6	6	27
7330939	ACPF/30x15 M8	30	15	M8	8	48
7330941	ACPF/30x20 M8	30	20	M8	8	40
7330942	ACPF/30x25 M8	30	25	M8	8	36
7330943	ACPF/30x30 M8	30	30	M8	8	31
7330944	ACPF/40x20 M8	40	20	M8	8	85
7330945	ACPF/40x30 M6	40	30	M6	6	75
7330947	ACPF/40x30 M8	40	30	M8	8	75
7330951	ACPF/40x30 M10	40	30	M10	10	75
7331140	ACPF/40x40 M8	40	40	M8	8	72
7331144	ACPF/50x20 M10	50	20	M10	10	110
7331148	ACPF/50x30 M10	50	30	M10	10	108
7331152	ACPF/50x40 M10	50	40	M10	10	106
7331156	ACPF/60x30 M12	60	30	M12	12	170
7331160	ACPF/75x25 M12	75	25	M12	12	310
7331164	ACPF/75x30 M12	75	30	M12	12	300
7331168	ACPF/75x40 M12	75	40	M12	12	290
7330953	ACPF/75x50 M12	75	50	M12	12	260
7331176	ACPF/75x55 M12	75	55	M12	12	250
7331180	ACPF/100x40 M16	100	40	M16	16	420
7331184	ACPF/100x50 M16	100	50	M16	16	400
7331188	ACPF/100x60 M16	100	60	M16	16	340

NOTE: Si forniscono, per quantità adeguate, durezze minori o superiori a 60 Shore A e inserti a misura.

For certain quantities, it can be supplied with a hardness higher or lower than 60 shore A and with inserts of different measures.

Por cantidad apropiada disponible también con dureza superior o inferior a 60 shore A y con insertos de distintas medidas.